

# HAWE

## New at HAWE Wester:

The Potato-Transfer trailer K UW 2000 has been completely redeveloped for quick and crop-friendly potato harvesting: With up to 30 m<sup>3</sup> loading capacity and the usual robust HAWE construction, the K UW 2000 offers an efficient and comfortable solution.

**HAWE-K UW 2000**  
**Potato-Transfer trailer**  
**Loading volume 22-30 m<sup>3</sup>**



## POTATO-TRANSFER TRAILER

TRANSPORTED BY PASSION

# For a quick and gentle potato harvesting



The stable frame construction with mounted steel container is equipped with a rolling floor with stable conveyor chain and galvanized steel strips. The cross elevator is 1200 mm wide and allows a discharge capacity of up to 120 t / h.



The transfer height is approx 4.1 m. the folding of the elevator belt allows a particularly gentle transfer into the receiving vehicle. The KUW is also suitable for other crops such as Carrots, Onions, Beetroot, Parsnips etc.



The collection bunker for trash and soil offers up to approx. 2m<sup>3</sup> volume. The bunker is emptied back in the field hydraulically via two discharge flaps.

## Specifications – potato transfer trailers



The adjustable roller distance on the roller separator optimizes the cleaning of the crop. Due to the variable angle of inclination, the cleaning performance or the charging speed can be set individually. The rollers are cleaned via a high-speed function.

Typ	KUW 2000
Permitted gross weight (t)	24
Capacity (m <sup>3</sup> )	22 - 24
<b>Body dimensions</b>	
Length (m)	7,10
Width (m)	2,40
<b>Overall dimensions</b>	
Length (m)	11,60
Width incl. tyres (m)	2,95
Height (m)	3,90
Brakes	Dual-circuit air brakes with ALB
<b>Running gear type</b>	BPW axles, tandem
Suspension	24 t Running gear with hydraulic suspension incl. lift axle
Steering axle(s)	1st & 2nd axle self-steering, hydr. lockable
<b>Attachment</b>	
Low-level K80	Serie
Drawbar suspension	Serie
<b>Tyres</b>	
Standard	710/50x26,5 16 PR
<b>Unloading belt</b>	
Length (m)	4,5
Unloading rate t/h	120



HAWE-Wester GmbH & Co. KG Maschinenbau  
 Zum Turm 16 · 26892 Wipplingen · Phone +49 (0)4966 / 91880  
 Fax +49 (0)4966 / 1211 · mail@hawe-wester.de · www.hawe-wester.de